

PATENT APPLICATION

**AN ANALYTICAL PARASITIC CONSTRAINTS GENERATION
TECHNIQUE**

Inventor(s): Pengfei Zhang, a citizen of the People's Republic of China, residing at
5300 Shamrock Common
Fremont, CA 94555

Xisheng Zhang, a citizen of the People's Republic of China, residing at
1336 Flicker Way
Sunnyvale, CA 94087

Yuping Wa, a citizen of the People's Republic of China, residing at
26 XinXi Road, Suite 1107
Beijing 100084, China

Assignee: Magma Design Automation, Inc.
1650 Technology Drive
San Jose, CA 95110

Entity: Large

AN ANALYTICAL PARASITIC CONSTRAINTS GENERATION TECHNIQUE

CROSS-REFERENCES TO RELATED APPLICATIONS

- 5 **[0001]** This application claims priority to and the benefit of the filing date of provisional patent application Serial No. 601442,308 filed Jan. 27, 2003.

BACKGROUND OF THE INVENTION

1. Field of the Invention

10

[0002] The present invention relates generally to constraints generation and more specifically it relates to an analytical parasitic constraint generation technique for parasitic loading constraints generation based on analytical assessment of circuit nodes time constants.

2. Description of the Related Art

15

[0003] It can be appreciated that constraints generation have been in use for years. Typically, constraints generation are comprised of manual estimation of acceptable amount of parasitic loading at critical nodes based on individual designer's experience and rule of thumb, or constraints generation based on extensive numerical circuit simulation and

20 sensitivity analysis at multiple circuit nodes.

[0004] The main problem with conventional constraints generation are manual estimation hinders productivity and error prone. Another problem with conventional constraints generation are numerical analysis is often not feasible due to the size and complexity of the circuit under consideration. Another problem with conventional constraints generation are

25 constraints generated with numerical analysis methodology sometimes are not achievable due to lack of physical meaning in the generation process.

[0005] While these devices may be suitable for the particular purpose to which they address, they are not as suitable for parasitic loading constraints generation based on analytical assessment of circuit nodes time constants. The main problem with conventional

30 constraints generation are manual estimation hinders productivity and error prone. Another problem is numerical analysis is often not feasible due to the size and complexity of the circuit under consideration. Also, another problem is constraints generated with numerical

analysis methodology sometimes are not achievable due to lack of physical meaning in the generation process.

[0006] In these respects, the analytical parasitic constraints generation technique according to the present invention substantially departs from the conventional concepts and designs of the prior art, and in so doing provides an apparatus primarily developed for the purpose of parasitic loading constraints generation based on analytical assessment of circuit nodes time constants.

BRIEF SUMMARY OF THE INVENTION

[0007] In view of the foregoing disadvantages inherent in the known types of constraint generation now present in the prior art, the present invention provides a new an analytical parasitic constraints generation technique construction wherein the same can be utilized for parasitic loading constraints generation based on analytical assessment of circuit nodes time constants.

[0008] The general purpose of the present invention, which will be described subsequently in greater detail, is to provide a new an analytical parasitic constraints generation technique that has many of the advantages of the constraints generation mentioned heretofore and many novel features that result in a new an analytical parasitic constraints generation technique which is not anticipated, rendered obvious, suggested, or even implied by any of the prior art constraints generation, either alone or in any combination thereof.

[0009] To attain this, the present invention generally comprises DC operating point simulation, open circuit time constant calculator, circuit bandwidth estimation, parasitic loading constraints generator. DC operating point simulation calculates the equivalent resistive impedance at each circuit node. The time constant calculator analytically assesses the time constant related to each circuit node based on open-circuit time constant technique. Circuit bandwidth estimation module estimates the bandwidth of the circuit based on the calculated time constants at each node and then compares with bandwidth requirement. Parasitic loading constraints generator calculates the tolerable excessive parasitic loading at each circuit node to be used in physical synthesis, or to select optimal circuit topology.

[0010] There has thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof may be better understood, and in order

that the present contribution to the art may be better appreciated. There are additional features of the invention that will be described hereinafter.

[0011] In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein are for the purpose of the description and should not be regarded as limiting.

[0012] A primary object of the present invention is to provide an analytical parasitic constraint generation technique that will overcome the shortcomings of the prior art devices.

[0013] An object of the present invention is to provide an analytical parasitic constraint generation technique in layout constrains generation with OCT (open circuit time) constant for critical nodes.

[0014] An object of the present invention is to provide an analytical parasitic constraint generation technique for parasitic loading constraints generation based on analytical assessment of circuit nodes time constants.

[0015] Another object is to provide an analytical parasitic constraint generation technique that explores quickly and analytically the candidate circuit topology for a matrix of performance specification, especially circuit bandwidth.

[0016] Another object is to provide an analytical parasitic constraint generation technique that generates parasitic loading constraints that can be used in physical synthesis.

[0017] Another object is to provide an analytical parasitic constraint generation technique that optimizes circuit performance quickly and analytically by running through what-if scenarios of placement options.

[0018] Another object is to provide an analytical parasitic constraint generation technique that selects the optimal routing solution by running through what-if scenarios quickly and analytically.

[0019] Another object is to provide an analytical parasitic constraint generation technique that selects optimal parasitic elements for optimizing tuning frequency response of a RF circuit.

[0020] Another object is to provide an analytical parasitic constraint generation technique that quickly analyzes circuit to identify the dominant pole(s) to assess the speed of an unknown circuit.

[0021] Other objects and advantages of the present invention will become obvious to the reader and it is intended that these objects and advantages be within the scope of the present invention.

[0022] To the accomplishment of the above and related objects, this invention may be embodied in the form illustrated in the accompanying drawings, attention being called to the fact, however, that the drawings are illustrative only, and that changes may be made in the specific construction illustrated.

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] Various other objects, features and attendant advantages of the present invention will become fully appreciated as the same becomes better understood when considered in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the several views, and wherein:

Fig. 1 [--] is one example of the Concept of Open Circuit Time Constant in one embodiment according to the present invention.

Fig.2 [--] is a flowchart of a method for Parasitic Loading Constraints Generation in one embodiment according to the present invention ~~Flow Chart.~~

Fig. 3 [--] is a flowchart of a method for ~~Means of~~ Circuit Physical Synthesis, Selecting Optimal Circuit Topology Parasitic Capacitance, Parasitic Inductance, and Routing Solution, and ~~Means of~~ Stability Analysis and Optimizing Circuit Performance in one embodiment according to the present invention ~~Flow Chart.~~

DETAILED DESCRIPTION OF THE INVENTION

[0027] Turning now descriptively to the drawings, in which similar reference characters denote similar elements throughout the several views, the attached figures illustrate an analytical parasitic constraint generation technique, which comprises DC operating point simulation, open circuit time constant calculator, circuit bandwidth estimation, parasitic loading constraints generator. Fig. 1 is one example of the Concept of Open Circuit Time Constant in one embodiment according to the present invention. Fig.2 is a flowchart of method 200 for Parasitic Loading Constraints Generation in one embodiment according to the present invention. In step 210, a netlist (e.g., netlist 215) is input. Netlist 215 may include ground/power pins, input/output pins, passive/active elements, and other terminals. In step 220, DC operating point simulation calculates the equivalent resistive impedance at each circuit node (e.g., the equivalent resistive impedance at node G of FIG. 1A is $r_G = (R_S + R_E)/(1 + g_m * R_E)$ and the equivalent resistive facing C_{gs} is $r_{gs} = R_L + R_S + g_m/(1 + g_m * R_E)$). In step 230, [[T]]the time constant calculator analytically assesses the time constant related to each circuit node based on open-circuit time constant technique. In step 240, Circuit bandwidth estimation module 255 estimates the bandwidth of the circuit based on the calculated time constants at each node and then compares with bandwidth requirement. In step 250, Parasitic loading constraints generator calculates the tolerable excessive parasitic loading 260 at each circuit node to be used in physical synthesis, or to select optimal circuit topology.

[0028] DC operating point simulation calculates the equivalent resistive impedance at each circuit node. Numerical simulator is called in to calculate DC operating point and thus the equivalent resistive impedance at each node. Numerical simulators can be one of the commercially available tools such as SPICE or Spectre. Built-in simulator is another alternative to calling external simulators, as DC operating point simulation is simple and fast.

[0029] The time constant calculator analytically assesses the time constant related to each circuit node based on open-circuit time constant technique. Open circuit time constant of each node in the circuit is calculated by multiply the equivalent resistive impedance at this circuit node with the total capacitance at the same node. An alternative is to perform a transient simulation with numerical simulator at each stage of the circuit and then calculate the time constant at each node.

[0030] Circuit bandwidth estimation module estimates the bandwidth of the circuit based on the calculated time constants at each node and then compares with ~~bandwidth~~ bandwidth requirement. As most circuits have a dominant pole, the bandwidth of the complete circuit can be approximated with the summation of the reciprocals of each time constant at each circuit node. Some exceptional circuit where open circuit time constant approach does not apply shall be identified and processed accordingly. Capacitive loading at various nodes can be user input information or automatic extracted values.

[0031] Parasitic loading constraints generator calculates the tolerable excessive parasitic loading at each circuit node to be used in physical synthesis, or to select optimal circuit topology. Comparing the bandwidth estimated with the circuit design specification, the maximum tolerable parasitic loading at each circuit node can be calculated, which can be used for circuit physical synthesis and/or circuit topology selection. In RF circuits, if inductive tuning load is used, the optimal parasitic capacitance can also be generated to achieve optimized tuning frequency response. However, if capacitive tuning load is used, the optimal parasitic inductance can also be generated to achieve optimized tuning frequency response. The same methodology can be expanded to stability analysis to generate an optimal range of the parasitic loading values. Components in this invention are suggested being used in series, i.e. to perform DC OP simulation and then to calculate time constant at each circuit node. The complete circuit bandwidth is then estimated and finally the parasitic loading constraints can be generated against a design specification. However, each component can be used separately in other context. Invention can be used to generate physical synthesis constraints. Invention can also be used in circuit optimization. Invention can be used in automatic circuit synthesis at initial topology exploration stage.

[0032] The required value of bandwidth is specified by the designer. a. The operating points catcher runs spice OP analysis to get the circuit operating points. b. The open-circuit time constant calculator calculates the open circuit time constant (Octime) according to the DC OP for each circuit stage. c. The overall circuit bandwidth calculator calculates the bandwidth, BWcalc without parasitics considered. d. The allowed maximum open-circuit time constant calculator calculates the allowed maximum open circuit time constant based on the formula for each stage. $Octime_new = Octime * BWcalc / Bwspec$ where Octime is open-circuit time constant without net-related parasitics considered, BWcalc is the bandwidth calculated without net-related parasitics, and Bwspec is the required bandwidth. e. The parasitic RCL calculator calculates the net-related parasitic resistance, capacitance, and

inductance for each net based on the OCtime_new, which is the reverse procedure to calculate the open-circuit time constant. f. The parasitic constraints on non-critical signal path also can be calculated by scaling the original OC time with BWcalc/BWspec. The parasitic constraints will be shown as the net parasitic resistance, capacitance, and inductance. And only when BWcalc is greater than BWspec, this automatic parasitic constraints generation method can be valid.

[0033] Fig. 3 is a flowchart of method 300 for Circuit Physical Synthesis, Selecting Optimal Circuit Topology Parasitic Capacitance, Parasitic Inductance, and Routing Solution, and Stability Analysis and Optimizing Circuit Performance in one embodiment according to the present invention. In step 305, a netlist is input. Step 310 includes a signal flow driven circuit analysis technique. Step 315 includes a signal flow driven circuit physical synthesis technique. Step 320 includes an analytical parasitic constraint generation technique. Step 325 includes circuit physical synthesis.

[0034] Step 330 includes a mean of selecting optimal circuit topology. Step 335 includes a mean of selecting optimal parasitic capacitance. Step 340 includes a mean of selecting optimal parasitic inductance. Step 345 includes a mean of selecting optimal routing solution. Step 350 includes a mean of stability analysis. Step 355 includes a mean of optimizing circuit performance.

[0035] As to a further discussion of the manner of usage and operation of the present invention, the same should be apparent from the above description. Accordingly, no further discussion relating to the manner of usage and operation will be provided.

[0036] With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of the invention, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by the present invention.

[0037] Therefore, the foregoing is considered as illustrative only of the principles of the invention. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the invention.

AN ANALYTICAL PARASITIC CONSTRAINTS GENERATION TECHNIQUE

ABSTRACT OF THE DISCLOSURE

An analytical parasitic constraint generation technique for parasitic loading constraints generation based on analytical assessment of circuit nodes time constants. The inventive device includes DC operating point simulation, open circuit time constant calculator, circuit bandwidth estimation, parasitic loading constraints generator. DC operating point simulation calculates the equivalent resistive impedance at each circuit node. The time constant calculator analytically assesses the time constant related to each circuit node based on open-circuit time constant technique. Circuit bandwidth estimation module estimates the bandwidth of the circuit based on the calculated time constants at each node and then compares with band-width requirement. Parasitic loading constraints generator calculates the tolerable excessive parasitic loading at each circuit node to be used in physical synthesis, or to select optimal circuit topology.

61268384 v1